DECLARATION OF PERFORMANCE



IN ACCORDANCE WITH CONSTRUCTION PRODUCTS GUIDELINE

N	lr	\cap	\cap	۱1
ıvı				, ,

1. Identification code of product type:	Ceramic tiles, extruded with low water absorption
	$0.5\% < E_h \le 3\%$, group Al _h attachment A,
	3% < E _b ≤ 6% group All _{a-1} attachment B,
	glazed (GL) and unglazed (UGL)
2. Intended use:	For indoor and outdoor floorings and wall coverings

System 4

3. Manufacturer: Ströher GmbH, Ströherstraße 2-10, 35683 Dillenburg 4. System(s) of assessment and verification

of constancy of performance in accordance with attachment V:

5. Harmonized standard: DIN EN 14411: 2012

6. DECLARED PERFORMANCES:

	_		
Essential characteristics	Performance		
Reaction to fire	A1 / A1 _{FL}		
Release of hazardous substances:			
- cadmium	NPD		
- lead	NPD		
- others	NPD		
Durability for:			
- indoor use	passed		
- outdoor use: resistance to freeze thaw cycles	passed		
Breaking load			
- Group Al _b attachment A	Thickness ≥ 7,5 mm: ≥ 1100 N		
- Group All _{a-1} attachment B	Thickness ≥ 7,5 mm: ≥ 950 N		
Slip resistance properties			
CEN/TS 16165 attachment A	NPD		
Tactility	NPD		
Bending strength/adhesion:			
- cementitious mortar, type C1	≥ 0,5 N/mm ²		
- dispersion adhesives	NPD		
- reaction resin adhesives	NPD		
- mortar	NPD		
Thermal shock resistance	passed		

^{7.} The performances of the above mentioned product correspond to the declared performances. This declaration of performance was issued in accordance with (EU) Regulation No. 305/2011 under the sole responsibility of the manufacturer stated above. Signed for and on behalf of the manufacturer by

Dirk Hümmer (Geschäftsführer) Name und Funktion

Dillenburg, 15.10.2020

Ort und Datum der Ausstellung

Ströher GmbH

Ströherstraße 2-10 35683 Dillenburg

Telefon: .+49 2771 391-0 Unterschriftelefax: +49 2771 391-340 E-Mail: info@stroeher.de

Internet: www.stroeher.de